AMADAS INDUSTRIES

2120

PULL-TYPE PEANUT COMBINE









2120: THE INDUSTRY STANDARD

The *AMADAS 2120™* is the latest generation of our class-leading wide body PT combine, the benchmark by which all others are measured. The 2120 has many features to enhance performance, and updates to increase uptime and reduce cost of operation. The 2120 is available with higher capacity baskets in both *BDS* (Bin Dump System) and *OCS* (Off-load Conveying System) and now with our patented *Double Swivel Tongue Gearbox* option, which offers unprecedented handling in the field. The *AMADAS 2120™* is the world's #1 high capacity combine for harvesting peanuts in all conditions, setting the industry standard for excellence.

2120 BENEFITS

- 8,750 lb. Dump Basket with increased tip height (13'6"), 100% more dirt screening area, and high strength construction: CNC punched panels, stainless steel peanut duct, and large service access panels
- New two-point quick hitch tongue with 200 HP rated Double Swivel Gearbox
- 8,500 lb. capacity OCS Basket with faster unloading (25% faster), and high strength construction: CNC punched panels, stainless steel peanut duct, large service access panels
- Single Chain Disc Separator Drive
- Heavy duty (20k) wheel hubs & Spindles with Goodyear radial tires

LENGTH OVERALL:	29' - 6"	WIDTH:	18' - 6"
HEIGHT (BIN LIP IN):	15' - 0"	HEIGHT (BIN LIP OUT):	16' - 5"
DUMP HEIGHT:	13' - 6"	SERVICE HEIGHT (BIN RAISED):	30' - 11"
WEIGHT (EMPTY):	25,000 LBS	HEADER WIDTHS:	18', 19'
INSIDE WORKING WIDTH:	96-1/4"	BIN CAPACITY:	8,750 LBS
TIRE SIZE (STD):	800/85 R32 HIGH FLOTATION CLEATED RADIAL	OPERATION/WARNING LIGHT KIT:	LED
REMOTE AUGER REVERSE:	STANDARD	VINE SPREADER	OPTIONAL
TONGUE:	• 200 HP RATED DOUBLE SWIVEL GEARBOX		
HITCH TYPE:	• TWO POINT QUICK HITCH		
PICKING:	• FOUR Ø30" SPRING-TOOTH PICKING CYLINDERS • DUAL SPEED CYLINDER DRIVES (OPTIONAL) • ADJUSTABLE RETENTION BOARD • TWO SETS ADJUSTABLE OVERHEAD TEETH (STANDARD) • FIVE SETS ADJUSTABLE CONCAVE BREAST SPRING TEETH (OPTIONAL)		
SEPARATION SYSTEM:	• FIVE RETRACTABLE SPRING TOOTH CYLINDERS • TWO BEATER CYLINDERS • 15-ROLL DISC SEPARATOR • Ø14" 24-BLADE CROSS INDUCTION CLEANING FAN		
ELEVATOR SYSTEM:	• Ø12" COLLECTION AUGER TO 9-1/2" SQUARE DUCT • Ø28"12-BLADE CENTRIFUGAL FAN		
PTO INPUT:	• 1000 RPM 1-3/4" -20, OR • 1000 RPM 1-3/8 -21		
PTO DRIVELINE:	• 790 RPM INPUT (STANDARD) • 850 RPM INPUT (OPTIONAL)		
TRACTOR REQUIREMENTS:	• PTO HORSEPOWER: 200+ • HYDRAULIC CAPACITY (OCS): 40GPM FLOW AT COMBINE PTO SPEED		

*Note: The above specifications are for an 8,750 lb. capacity Bin Dump equipped combine.
Visit us online for more product information.